


DISPLACEMENT 2.0L 7.0L
HORSEPOWER 525 1150

2000
1900
1800
1700
1600
1500
1400
1300
1200
1100
1000
900
800
700
600
500
400
300
200
100
0



This Turbocharger is Ideal for:



- Forged, fully-machined compressor wheel featuring next generation aerodynamics
- Dual ball bearing, oil & water-cooled CHRA
- Free float, non-wastegated turbine housing
- Optional turbine housings with T4 or diesel turbine inlet flange
- Turbine wheel cast from "Inconel" material for extreme applications
- Ported shroud compressor housing to increase surge resistance
- Outline interchangeable with the ball bearing GT4202R
- GTX4202R is sold without turbine housing, includes CHRA & compressor housing. Turbine housing kits are available

FLANGE	INLET		OUTLET		
	Component	Page	Diagram	Page	Diagram
Compressor	89	37	89	07	
Turbine		See		Note	
Oil	91	17	91	06	
Water	93	14	93	14	

GTX4202R		COMPRESSOR				TURBINE		
Turbo PN	CHRA PN	Ind Whl Dia	Exd Whl Dia	Trim	A/R	Whl Dia	Trim	A/R
800269-2	451888-44	75.8mm	102.3mm	55	0.60	82.0mm	84	-

TURBINE HOUSING OPTIONS

PN	A/R
757707-1*	1.01
757707-2*	1.15
757707-3*	1.28
757707-4*	1.44
757707-9*	1.15

